

MID VOLTAGE CMC 2012 (0805) SERIES

Rated Voltage: 500V

| Part No. | Capacitance (PF) | Tolerance | Thickness (mm) |
|------------------|---------------------|-----------|-------------------|
| CMC 2012CG 2H100 | * | 10 | D 0.6±0.10 |
| CMC 2012CG 2H120 | * | 12 | J, K 0.6±0.10 |
| CMC 2012CG 2H150 | * | 15 | J, K 0.6±0.10 |
| CMC 2012CG 2H180 | * | 18 | J, K 0.8±0.10 |
| CMC 2012CG 2H220 | * | 22 | J, K 0.8±0.10 |
| CMC 2012CG 2H270 | * | 27 | J, K 0.8±0.10 |
| CMC 2012CG 2H330 | * | 33 | J, K 0.8±0.10 |
| CMC 2012CG 2H390 | * | 39 | J, K 0.8±0.10 |
| CMC 2012CG 2H470 | * | 47 | J, K 0.8±0.10 |
| CMC 2012CG 2H560 | * | 56 | J, K 0.8±0.10 |
| CMC 2012CG 2H680 | * | 68 | J, K 0.8±0.10 |
| CMC 2012CG 2H820 | * | 82 | J, K 0.8±0.10 |
| CMC 2012CG 2H101 | * | 100 | J, K 0.8±0.10 |
| CMC 2012CG 2H121 | * | 120 | J, K 1.0±0.15 |
| CMC 2012CG 2H151 | * | 150 | J, K 1.0±0.15 |
| CMC 2012CG 2H181 | * | 180 | J, K 1.2±0.15 |
| CMC 2012CG 2H221 | * | 220 | J, K 1.2±0.15 |
| CMC 2012CG 2H271 | * | 270 | J, K 1.2±0.15 |
| CMC 2012CG 2H331 | * | 330 | J, K 1.2±0.15 |
| CMC 2012CG 2H391 | * | 390 | J, K 1.2±0.15 |
| CMC 2012CG 2H471 | * | 470 | J, K 1.2±0.15 |
| CMC 2012CG 2E561 | * | 560 | J, K 1.0±0.15 |
| CMC 2012CG 2E681 | * | 680 | J, K 1.0±0.15 |
| CMC 2012CG 2E821 | * | 820 | J, K 1.2±0.15 |
| CMC 2012CG 2E102 | * | 1000 | J, K 1.2±0.15 |